



UNO POWER power supplies

Basic functionality compact

UNO POWER

Compact and highly efficient

Wide range of products

- for all common voltage levels

Save energy

- thanks to high efficiency of up to 94 % and low power dissipation (no-load) of less than 0.3 W

Save space

- Power density up to 325 W/dm³

High reliability

- Wide temperature range from -25 to +70 °C

UNO POWER 1~

	
24 DC / 150 W	24 DC / 240 W
UNO-PS/1AC/24DC/150W 2904376	UNO-PS/1AC/24DC/240W 2904372

UNO POWER 1~

				
24 DC / 30 W	24 DC / 60 W	24 DC / 100 W	24 DC / 90 W	24 DC / 90 W
UNO-PS/1AC/24DC/30W 2902991	UNO-PS/1AC/24DC/60W 2902992	UNO-PS/1AC/24DC/100W 2902993	UNO-PS/1AC/24DC/90W/C2LPS 2902994	UNO-PS/2AC/24DC/90W/C2LPS 2904371
	48 DC / 60 W	48 DC / 100 W		
	UNO-PS/1AC/48DC/60W 2902995	UNO-PS/1AC/48DC/100W 2902996		
15 DC / 30 W	15 DC / 55 W	15 DC / 100 W		
UNO-PS/1AC/15DC/30W 2903000	UNO-PS/1AC/15DC/55W 2903001	UNO-PS/1AC/15DC/100W 2903002		
12 DC / 30 W	12 DC / 55 W	12 DC / 100 W		
UNO-PS/1AC/12DC/30W 2902998	UNO-PS/1AC/12DC/55W 2902999	UNO-PS/1AC/12DC/100W 2902997		
5 DC / 25 W	5 DC / 40 W			
UNO-PS/1AC/5DC/25W 2904374	UNO-PS/1AC/5DC/40W 2904375			

PHOENIX CONTACT GmbH & Co. KG
 Flachsmarktstraße 8
 32825 Blomberg, Germany
 Phone: +49 (0) 52 35 3-00
 Fax: +49 (0) 52 35 3-4 12 00
 E-mail: info@phoenixcontact.com
phoenixcontact.com