The smallest-ever touch screen terminal!

Magelis STO

Small graphic terminal, configured by Vijeo Designer





Compact shape packed with features

Schneider Electric[™] new range of touch screen Small Panels offers you greater ease of use and efficiency while retaining the inherent features of the HMI range.

> Tool-free installation

Terminals are mounted easily onto your enclosure using spring clips.



Two monochrome versions are available in three colours — green/orange/red or white/pink/red — for enhanced readability. Several levels of grey, numerous character fonts, and $Vijeo^{TM}$ Designer's extensive object library all help to provide exceedingly high-quality graphic animations.

> One international software tool

Available in more than 15 languages, all Vijeo Designer elements are available directly from the demonstration software via a simple download.

> Ease of maintenance

- > No batteries required, backlit by LEDs
- > Removable power connector
- > USB memory stick for application downloads

> Communication capability

- > Standard RJ45 serial port with Modbus, Zelio™ link, Ethernet protocols, and other commercially-available third-party protocols
- > 2 USB ports: 1 mini B port for downloading and 1 standard A port for USB memory stick and USB peripherals







Serial link STO







> Selection guide

Description	Magelis™ STO	
Screen	3.4", 200x80 resolution, monochrome, analogue touch panel	
Backlighting	LED 50,000 hours, 3 colours (green/orange/red)	LED 50,000 hours, 3 colours (white/pink/red)
НМІ	Multiprotocole serial link RJ45 RS485/232, 1 miniUSB Device + 1 USB Host V2.0	
Protocols	Modbus, Uni-Telway, Siemens PPI-MPI, Omron Sysmacway Rockwell DF1/DH485, Mitsubishi Melsec FX/Q/A	
Memory	Application + Backup: 16 MB FLASH	
Power supply	24 VDC with removable connector	
External dimensions	L113 x H78 x D28	
Product references	HMI STO511	HMI STO512


Ethernet STO



> Selection guide

Description	Magelis STO	
Screen	3.4", 200x80 resolution, monochrome, analogue touch panel	
Backlighting	LED 50,000 hours, 3 colours (green/orange/red)	LED 50,000 hours, 3 colours (white/pink/red)
НМІ	Ethernet, 1 miniUSB Device + 1 USB Host V2.0	
Protocols	TCP/IP, XWAY TCP/IP, PacDrive Ethernet, Mitsubishi Melsec Ethernet Q/A, Siemens SIMATIC S7 Ethernet, Omron Ethernet, Rockwell Ethernet IP	
Memory	Application + Backup: 16 MB FLASH	
Power supply	24 VDC with removable connector	
External dimensions	L113 x H78 x D28	
Product references	HMI STO531	HMI STO532

Zelio link STO



> Selection guide

Description	Magelis STO	
Screen	3.4", 200x80 resolution, monochrome, analogue touch panel	
Backlighting	LED 50,000 hours, 3 colours (green/orange/red)	
НМІ	Zelio link, 1 miniUSB Device + 1 USB Host V2.0	
Protocols	Zelio	
Memory	Application + Backup: 16 MB FLASH	
Power supply	24 VDC with removable connector	
External dimensions	L113 x H78 x D28	
Product references	HMI STO501	

> Accessories

Description	Reference
USB transfer cable	BMXXCAUSBH018
Spring clips	XBTZ3002
Screen protector	HMIZS60
Mini-USB extension cable	HMIZSUSBB
Serial printer cable	HMIZURS
Communication cable for Zelio	SR2CBL09

Schneider Electric Industries SAS

Head office 35, rue Joseph Monier - CS30323 F92505 Rueil-Malmaison Cedex FRANCE

www.schneider-electric.com

Due to possible modifications of standards and equipment, characteristics described in the text and illustrations in this document must be confirmed by Schneider Electric. Publication: Schneider Electric

Printing:

©2011 Schneider Electric. All Rights Reserved. Schneider Electric, Vijeo, Magelis, and Zelio are trademarks owned by Schneider Electric Industries SAS or its affiliated companies. All other trademarks are property of their respective owners.