



Technical Data Sheet

STRUCK - N

Composition : Celluloid Preparation of Salt of Oleic Acids and Amides.
Does not contain any petroleum/Bituminous Oil.

Specification	25 %	30 %
Appearance	Pale White free flowing liquid.	Pale White free flowing liquid.
pH	9 -10	9-10
Soild Content	25 ± 2%	30 ± 2%

Dosages :

- For soft compounds like sponge compound sheets concentration of 1 part by weight Struck - N in 5 parts by weight of water can be used.
- Extruded hoses can be dipped in an aqueous solution of 1 part by weight of Struck - N in 3 to 6 part by weight of water.

Uses and Benefits :

- Used as an anti-tack agent for uncured rubber sheets of mixed compounds.
- It prevents sticking of compounded sheets, semi-finished goods and extruded articles to each other.

Application

- Struck - N is to be used in diluted form.
- It is to be diluted with water to get desired concentration.
- This Aqueous solution can be used by spraying, Brushing, Dipping.

Packing : 50kg or 200kg MS drum.

Storage stability : Up to 1 years in normal storage conditions.

Approvals : **SVHC**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Struck - N.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzinculet.com Visit us at: www.pukhrajzinculet.com