



## Technical Data Sheet

### STRUCK – N 20

**Composition** : Struck N 20 is a water based product without organic volatile solvent used to avoid typical moulding defects which appear during the tyre vulcanization process.

**Specification** : Appearance : Black liquid  
pH : 7.5 to 8.5  
Total Solids : 20± 3%

**Uses and Benefits** :

- Used as outside paint in tyre applications.
- Homogenize the product in the original drum by stirring it.
- Apply it over the tire sidewalls by means of conventional spray equipment and allow drying before curing operation. Drying time is 30 min.

**Packing** : 50kg or 200kg PVC drum.

**Storage stability** : Up to 6 month in normal storage conditions

**Handling** : Consult material safety data sheet (MSDS) for additional handling information for Struck – N 20.

#### PUKHRAJ ADDITIVES LLP

*An ISO 9001:2008 Certified Company*

5B, 5<sup>th</sup> Floor, Diamond House, Plot No. 515, Behind National College,  
TPS III, 35<sup>th</sup> Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: [info@pukhrajzinculet.com](mailto:info@pukhrajzinculet.com) Visit us at: [www.pukhrajzinculet.com](http://www.pukhrajzinculet.com)