



## Technical Data Sheet

### STRUCK – N 50

**Composition** : Water dispersible inorganic based compound

<b>Specification</b>	<b>50 %</b>	<b>45 %</b>
Appearance	Blackish Grey/Beige Liquid	Blackish Grey/Beige Liquid
pH	7 to 8	7 to 8
Total Solids	50± 2%	45± 2%

**Uses and Benefits** :

- Used as application paint on inside of green tyre by spraying.
- Allow enough drying time before taking the green tyre for further processing.

**Important Note** : Roll the drum before use and filter before spray.

**Packing** : 50kg or 200kg PVC drum.

**Storage stability** : Up to 6 months in normal storage conditions.

**Handling** : Consult material safety data sheet (MSDS) for additional handling information for Struck – N 50.

#### **PUKHRAJ ADDITIVES LLP**

*An ISO 9001:2008 Certified Company*

5B, 5<sup>th</sup> Floor, Diamond House, Plot No. 515, Behind National College,  
TPS III, 35<sup>th</sup> Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: [info@pukhrajzincolet.com](mailto:info@pukhrajzincolet.com) Visit us at: [www.pukhrajzincolet.com](http://www.pukhrajzincolet.com)