



Zincolet - 280

Processing Additives

Composition : Organo-silicone compound based on special fatty acid derivatives and silicones (75 %) on inorganic carrier (25%).

Specification : Colour (Visible) : Light Brown to White
Appearance : Crumb powder

Dosage :
• 0.5 – 2 phr.

Uses and Benefits :

- Highly effective process and mould release agent for special polymers.
- Particularly good effect in fluorinated rubber and acrylate rubber.
- Zincolet 280 has extremely Low volatility at high temperatures and particularly suitable for FKM.
- Gives excellent release properties on mixing machinery, exceptionally good flow and reduce mould fouling.

Packing : 25 kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 1 years in normal storage conditions.

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet - 280.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com