



Zincolet - RE

Processing Additives

Composition : Blend of dark aliphatic and aromatic hydrocarbon resins

Specification :

Appearance	:	Dark brown to Blackish brown flakes/Pellets
Softening point	:	100 ± 5°C
Ash content (2hrs,@850°C)	:	2% Max
Specific gravity	:	1.06

Dosage :

- 4 – 15phr

Uses and Benefits :

- It improves the homogeneity of polymers blend improving the process behavior.
- It gives very good compound tack.
- Zincolet - RE is compatible with NR, SBR, NBR, CR, EPDM, BR.
- Zincolet - RE is useful in blending two polymers with different polarities and viscosities.
- Zincolet - RE does not harden during vulcanization.

Packing : 25kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Up to 2 years in normal storage conditions.

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet - RE.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College, TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com