




Technical Data Sheet
Processing Additives

Zincolet -700

Composition : Zinc soap of mixed fatty acids with inorganic fillers.

Specification : Appearance : Beige to Creamish Flakes
Drop Point : $100 \pm 5^{\circ}\text{C}$
Ash content : $16.5 \pm 1\%$
(2hrs,@850°C)

Dosage :
• 2 – 5 Phr

Uses and Benefits :

- Zincolet - 700 is a very effective dispersing aid for white fillers. It is particularly effective in highly loaded Silica compounds.
- Zincolet - 700 if applied at the recommended dosage, does not bloom from vulcanisates due to its high solubility level.
- In the presence of silane coupling agents, Zincolet - 700 should be added after the silanisation process is completed.

Packing : 25kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years in normal storage conditions.

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet-700.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com