



Processing Additives

| Composition | : | Combination of higher molecular esters and amides. |
|--------------------------------|---|--|
| Specification | : | Color:Creamish ColorAppearance:FlakesDrop Point: $75 \pm 5 \circ C$ Ash content: 0.5% Max |
| Dosage | : | • 1- 4 phr |
| Uses and Benefits | : | |
| | • | Zincolet - A has a dispersing effect on fillers and improves flow and extrusion properties of rubber compounds, without having a peptizing or activating effect on vulcanization.Zincolet - A has proved helpful in Silica Compounds. It is suitable for polymers such as Neoprene, HNBR and ACM Viton. |
| Packing | : | 25kg Polylinedpolywoven bag / Polylined paper bag. |
| Storage stability Approvals | : | Upto 2 years in normal storage conditions. REACH/ROHS |
| Handling | : | Consult material safety data sheet (MSDS) for additional |

handling information for Zincolet-A.

PUKHRAJ ADDITIVES LLP

<u>An ISO 9001:2008 Certified Company</u> 5B, 5th Floor, Diamond House, Plot No. 515, Behind National College, TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA). ■Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com

Information provided herein is based upon tests believed to be reliable. We have no control over the manner in which others may use this information, it does not guarantee the results to be obtained. The company assumes no obligation or liability for the information in this document. No warranties are given, all implied warranties of merchantability or fitness for a particular purpose are expressly excluded.