



Zincolet - AA 16



Technical Data Sheet Processing Additives

Composition : Mixture of fatty soaps and amides predominantly calcium.

Specification :

Appearance	: Creamish color flakes.
Melting Point	: $100 \pm 5^{\circ}\text{C}$
Ash content	: $5 \pm 1\%$
Specific Gravity	: 1.00

Dosage :

- 1 – 3 phr.

Uses and Benefits :

- Improves flow of compound in transfer, compression and injection moulding.
- Prevents sticking of compounds to mill rolls.
- Gives good mould flow and improves viscosity.
- Reduces internal friction resulting in lowering energy consumption and mixing temperature.

Recommended for -
NR, SBR, EPDM, CR, IR, CM, ACM, As well as thermoplastic Elastomers.

Packing : 25 kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years in normal storage conditions.

Approvals : **REACH**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet-AA 16.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com