



Zincolet - D5

Processing Additives

Composition : Mixture of Zinc salt fatty acid, amides, esters with inorganic fillers

Specification	: Appearance	Beige brown Flakes
	Drop Point	85 ± 10°C
	Ash content (2hrs,@850°C)	25 ± 3%

Dosage :
• 2.0 – 3.0 phr.

Uses and Benefits :

- It reduces compound viscosity and improves flow properties.
- Improves flow of compound in transfer, compression and injection molding.
- Prevents sticking of compounds to mill rolls.
- Reduces internal friction resulting in lowering energy consumption and mixing temperature.

Recommended for -
NR, SBR, EPDM, EVA.

Packing : 25kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years in normal storage conditions.

Approvals : **REACH**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet - D5.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com