



Zincolet - X50NS

Processing Additives

Composition : Mixture of Organo-Silane and processing additives (50:50)

Specification :

Appearance	: Creamish Flakes
Drop Point	: $85 \pm 5^{\circ}\text{C}$
Ash content	: $25 \pm 2\%$
Specific Gravity	: 1.0

Uses and Benefits :

- Zincolet - X50NS is used to improve the physical properties of sulphur cured compounds and establish the chemical link between rubber and silica.
- Mechanical properties, e.g. modulus, compression set, tensile strength, abrasion resistance can be significantly increase by using Zincolet - X50NS.
- Enhance flow and release in fluoro elastomer processing.
- Acts as lubricant for fluoro and acrylate rubber.
- Zincolet - X50NS is especially suitable to improve the reinforcing properties of fillers that contain hydroxyl group in all unsaturated polymers having double bonds or their blends.

Packing : 25 kg Polylinedpolywoven bag / Polylined paper bag.

Storage stability : Upto 2 years In normal storage conditions.

Approvals : **REACH**

Handling : Consult material safety data sheet (MSDS) for additional handling information for Zincolet - X50NS.

PUKHRAJ ADDITIVES LLP

An ISO 9001:2008 Certified Company

5B, 5th Floor, Diamond House, Plot No. 515, Behind National College,
TPS III, 35th Road, Bandra (W), Mumbai, Maharashtra - 400 050 (INDIA).

Tel: +91-9833538089/+91-22-26494911/26494912/26494913

Email: info@pukhrajzincolet.com Visit us at: www.pukhrajzincolet.com