

EFFICIENT PERFORMANCE

SHARPLEX FILTERS (INDIA) PVT. LTD.

113



-1

Automatic discharge of cake



Saving of oil / Moisture in cake



Dry or wet cake discharge possible

✦ No requirement of filter cloth

Butterfly valve or wedge lock closing at bottom with or without heel leaf

Higher Filtration rate

Less installation area

Fixed or oscillating sluicing for wet cake discharge

CAPACITY 1m² to 125m²






<image>

Sharplex vertical pressure leaf filter features vertical pressure vessel, vertically placed filter leafs, pneumatic vibrating assembly, manifold and butterfly valve with actuator.

Filters are designed as per ASME, AD Merkblatter DIN, Tema.

Material of Construction : Stainless steel, carbon steel with rubber, PP, PVDF lining, Monel, Inconel, etc. Leafs in stainless steel 304, 316, 316L, 904L and material as per requirement. 'O' ring sealings are available in BUNA-N, Viton, EPDM, Nitrile, Silicon, HNBR etc. Filtration areas from 1m² to 125m² can be supplied. Dry or wet cake discharge is possible.







APPLICATIONS

Bleaching Earth/ Activated Carbon

- Resins
- → → Crude oil
- Molten Sulphur
- Ni-catalyst



Vertical pressure leaf filter with sluicing arrangement

Butterfly valve with rotary pneumatic actuator



MODELS & SPECIFICATIONS

Sr No.	Model SFV	FILTER AREA (M2)	LEAF SPACING (M2)	CAKE VOLUME (liters)	Empty Weights (Kg)
1	SFV/480/920/2/5	2	70	50	200
2	SFV/790/920/5/5	5	70	125	700
3	SFV/900/920/8/7	8	70	200	850
4	SFV/900/920/10/9	10	70	250	850
5	SFV/900/920/12.5/11	12.5	70	310	850
6	SFV/800/1500/15/9	15	75	375	500
7	SFV/1100/1250/15/9	15	70	375	800
8	SFV/1100/1250/20/11	20	70	500	800
9	SFV/1220/1250/25/11	25	70	625	1050
10	SFV/1220/1250/30/15	30	70	750	1050
11	SFV/1380/1350/35/13	35	75	875	2000
12	SFV/1380/1350/38.5/15	38.5	75	950	2000
13	SFV/1500/1500/42/13	42	75	1050	2100
14	SFV/1500/1500/46/15	46	75	1150	2100
15	SFV/1500/1500/50/17	50	75	1250	2100
16	SFV/1500/1650/60/17	60	75	1500	2500
17	SFV/1650/1500/70/19	70	75	1750	2150
18	SFV/1650/1800/70/16	70	75	1750	2150
19	SFV/1650/1800/78/18	78	75	1950	2150
20	SFV/1850/1800/85/16	85	75	2125	2900
21	SFV/1850/1800/90/18	90	75	2250	2900
22	SFV/1850/1800/100/20	100	75	2500	2900
23	SFV/2000/1800/120/22	120	75	2875	5000
24	SFV/2000/1800/125/24	125	75	3125	5000

INSTALLATIONS



Installation in edible oil plant



Installation in chemical plant





Installation in edible oil plant



FILTER LEAFS

THE HEART of pressure leaf filter

Filter Leafs are manufactured in house in Sharplex. The keyhole channel (frame) of filter leaf is also in house manufactured in CNC machine. Leafs are riveted on automatic riveting machine with 3 layers or 5 layers design. The filtration meshes used are of higher thickness to give extra rigidity to filter elements. The leafs are manufactured in SS304, SS316L, SS904L, Titanium, Monel etc. The top mesh used can be dutch woven mesh 24 x110, 60 mesh or PZ80. Leafs also can be enveloped with filter cloths for fine filtration. Leafs are manufactured under strict quality control to give you an highest quality product. Remeshing also carried out at our premises with latest techniques.

















8



250

6 5 5 5 6 6 6 6 6 6 6


9

TECHNICAL SPECIFICATIONS

Sr No.	Model SFV	FILTER AREA (m²)	Α	В	С	D	E	F
1	SFV/480/920/2/5	2	1350	2050	3150	1090	1600	2350
2	SFV/790/920/5/5	5	1390	2175	3150	2208	1600	3015
3	SFV/900/920/8/7	8	1450	2350	3150	2470	1970	3110
4	SFV/900/920/10/9	10	1450	2350	3150	2470	1970	3110
5	SFV/900/920/12.5/11	12.5	1450	2350	3150	2470	1970	3110
6	SFV/800/1500/15/9	15	1975	2780	4460	2470	1970	3035
7	SFV/1100/1250/15/9	15	1750	2700	4110	2810	1285	3560
8	SFV/1100/1250/20/11	20	1750	2700	4110	2810	1285	3560
9	SFV/1220/1250/25/11	25	1875	2930	4350	3030	2300	3855
10	SFV/1220/1250/30/15	.30	1875	2930	4350	3030	2300	3855
11 .	SFV/1380/1350/35/13	35	1890	3150	4580	3620	2866	4150
12	SFV/1380/1350/38.5/15	38.5	1890	3150	4580	3620	2866	4150
13	SFV/1500/1500/42/13	42	2050	3295	4950	3590	2915	4425
14	SFV/1500/1500/46/15	46	2050	3295	4950	3590	2915	4425
15	SFV/1500/1500/50/17	50	2050	3295	4950	3590	2915	4425
16	SFV/1500/1650/60/17	60	2200	3295	4950	3590	2915	4425
17	SFV/1650/1500/70/19	70	2470	3425	5400	3950	3140	4725
18	SFV/1650/1800/70/16	70	2470	3425	5400	3950	3140	4725
19	SFV/1650/1800/78/18	78	2470	3425	5400	3950	3140	4725
20	SFV/1850/1800/85/16	85	2500	4175	6135	4260	3710	5100
21	SFV/1850/1800/90/18	90	2500	4175	6135	4260	3710	5100
22	SFV/1850/1800/100/20	100	2500	4175	4175	4260	3710	5100

0


150



(Above is for typical orientation)



FLOW DIAGRAM OF CONTINUOUS FILTRATION PLANT





Sharplex was incorporated in February 1993 with a determination to make a mark in process filtration equipments, that are efficient and economical, catering to food, pharma, chemical, edible oil, fertilizer, petroleum & mining industries. Sharplex offers you the widest and most advanced range of process filtration equipments. The registered office & factory at Navi Mumbai are well equipped with a full fledged CAD center as well as sophisticated facility for testing, all regulated by a stringent quality policy, in turn enabling Sharplex to design each equipment to its perfection. Sharplex modern workshop at Navi Mumbai is "PED" approved by Lloyd's register.

An excellent team of skilled designers facilitates Sharplex to offer a wide variety of process filtration equipments like **Pressure Leaf Filter**, **Candle Filter**, **Horizontal Plate Filter**, **Polishing Filter**, **Tubular centrifuge**, **Nutsche filter & Vibroscreen**.





SHARPLEX FILTERS (INDIA) PVT. LTD. AN ISO 9001: 2008 COMPANY



signsmith/sfpl/vplf/0113/2k

R-664, T.T.C. Industrial Area, Thane Belapur, Rabale MIDC, Navi Mumbai - 400 701, India. Tel. : +91-22-2769 6339 / 2769 6322 / 2769 6331 | Fax : +91-22-2769 6325 Email : sharplex@vsnl.com

www.sharplex.com