FTM SS - GMP

A New Generation CE certified Semi Automatic Carton Sealing Machine



Features and Advantages

- Made of SS 304 GMP standard
- Reliable, robust design longer life
- Auto-Off Switch power saving
- Carton Counter with electronic digital display unit
- Positive top and bottom drive for sealing tall and heavy cartons as also regular cartons
- Easy belt replacements for quick maintenance
- Belt speed of 20m/minute-internationally benchmarked
- Belt Guards for safety
- Inbuilt Tool Box for ease of maintenance
- Telescopic legs precision bed height adjustment





FTM SS - GMP

A New Generation CE certified Semi Automatic Carton Sealing Machine

Specifications			
Spoomoutons	Minimum	Maximum	
Carton size (mm)			
Length	150	Unlimited	
Width	160	550	
Height	100	550	
Carton weight carrying capacity(Kg)	5	50	
NB: Any carton size approaching the follow $\frac{\text{Length of the carton}}{\text{Height of the carton}} > 0.6$	wing limits should be	test run to assure performance	
Machine Length (mm)		1080	
Machine Width (mm)		800	
Machine Height (mm)		1550	
Motors		2 Nos. of 0.25 HP (Geared)	
Voltage/Frequency		230V AC, 1 PH 50 Hz	
Power Consumption		360 Watts	

Options

- Entry or exit conveyors of stainless steel. Length: 0.5 Meter or 1 Meter.
- Taping heads for 63.5 mm (2.5") or 76.2 mm (3") BOPP Tape.

Applications

- Specially designed for Pharmaceutical and Food industries to meet GMP requirements.
- Recommended for use with Signode's PACKRITE[™] BOPP tape available in 650 M / 1000 M rolls





Equipment • Consumables • Services
ITW India Limited

Industrial Packaging Systems Group

401 & 402, New Udyog Mandir, Moghal Lane, Mahim, Mumbai 400 016, India Phone: 91-22-2444 9502/9022, Fax: 91-22-2444 9021

E-mail: in fo@itwindia.com

The company has a policy of continuous product development and reserves the right to alter specifications any time without prior notice