

HBX-4330TM

Automatic plastic strapping machine

Up to
70
straps per
minute!

- **Unmatched simplicity**
Easy to operate and maintain
- **Jam-resistant technology**
- **Bi-directional coil loading**



The new HBX-4330 automatic strapping machine is the simplest, most reliable general-duty strapping machine on the market today. With 40% fewer parts and more timesaving features, the HBX-4330 machine simplifies operation and maintenance to save you time and money.

TW Signode
Packaging Solutions
Equipment • Consumables • Services

HBX-4330TM Automatic plastic strapping machine

Unmatched simplicity

The HBX-4330's simple yet durable design eliminates the use of drive belts and clutches. This combined with other trouble-free maintenance elements like toolless hot knife removal and jam-resistant technology make it easier to operate and more cost effective to maintain than other strapping machines



Bi-directional coil loading

Strap coil pays off from either direction, eliminating the downtime and material waste resulting from incorrect coil loading.

Out-of-strap feature

The out-of-strap feature ejects the strap at the end of the coil to eliminate downtime and errors associated with removing the excess strap left in the machine.

Variable speed conveyor

The HBX-4330's standard variable reversible conveyor easily integrates with your existing conveyor system providing for easy set-up and operation

Fully accessible strap path

No tools required. Simply raise the tabletop and lift guide for access to strap path.



Toolless conveyor removal

Conveyors can be easily removed for maintenance.

Automatic cut-off and refeed option


Signode's patented automatic cut-off and refeed feature automatically ejects misfed strap, rethreads itself and continues strapping without operator intervention.

Save on strapping costs with HB Series plastic strapping

The new HBX-4330 utilizes Signode's newest Contrax[®] polypropylene strapping. HB Series strapping has the same durable properties as regular Contrax with more strap per coil.

HB 612 9mm Contrax coils - 4,877 meters per coil

HB 812 12mm Contrax coils - 3,658 meters per coil



HBX-4330 Chute inner dimensions

	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm
A*	20	510	28	710	33	840	48	1220	48	1220
B	15	380	20	510	30	760	20	510	48	1220

*Inner dimension A is maximum package size.

HBX-4330 Specifications

Cycle rate: Up to 70 straps per minute. Actual production will vary depending on package size, chute size and operator dexterity

Maximum package weight: 45.45 kgs on machine or conveyor

Maximum applied tension: Upto 113.63 kgs

Strapping: 9mm or 12mm Contrax polypropylene strapping

Electrical requirements:

120 volt, 60Hz, FLA 9.0 amp; 3 phase optional

Shipping weight: 272.73 kgs

HBX-4330 Options

- Single or dual compression
Single: Up to 54.55 kgs at 40.9 kgs psi
Dual: Up to 109.09 kgs at 40.9 kgs psi
- Indicator light alerts operator to low strap/out-of-strap conditions and machine malfunction
- EZ height adjustable leg kit - 26" to 40" (660mm to 1015mm)
- Automatic cut-off and refeed
- Conveyor interlock kit

The HBX-4330 is also available in a stainless steel model as well as a semiautomatic model, the HBX-4300.

ITW Signode
Packaging Solutions
Equipment • Consumables • Services

ITW India Limited
Industrial Packaging Systems Group

401&402 New Udyog Mandir, Moghul Lane, Mahim, Mumbai-400 016

Tel : 91-22-24449502, 24449022, Fax: 91-22-24449021

Email : info@itwindia.com, URL : www.itwsignodeindia.co.in

The Company has a policy of continuous product development and reserves the right to alter specifications without prior notice

Branches : Bangalore : 22240490/22242304, Bhilai : 2265318, Chennai : 64514401/24725313, Hyderabad : 30485200, Jamshedpur : 2361198/6453401, Kolkata : 23209374, Navi Mumbai : 27725740/6524, New Delhi : 26424984/26424990, Pune : 65105104, Rourkela : 6450388/2470757.