

TAPING & STRAPPING SYSTEM

An Economic Solution to Your Taping & Strapping needs



Features and Benefits

Self Centering mechanism

Extended side drive holds cartons for better strapping

Logic Control through PLC

Elimination of powered roller conveyor between taping and strapping equipment improves throughput


Straps and tapes up to 8 cartons per minute

Zero, one or two straps can be applied

Machines can be used on line, stand alone or separately

TAPING & STRAPPING SYSTEM

An Economic Solution to Your Taping & Strapping needs




Options

- System auto stop and carton counter
- Powerised top drive for cartons having weight between 40 to 60 kgs
- Idler roller conveyor attachment for CSM to use it stand-alone
- Three straps

System Specifications

Machine Size	1313(L) x 900(W) x 1715(H)
Power Supply	3 phase, 415V, 50Hz
Carton Length (mm)	300 to 700
Carton Width (mm)	200 to 500
Carton Height (mm)	150 to 500
Carton Weight (kg)	5 to 40
Belt Speed	20 meters/minute
Tape Size	2", 2 ½" or 3"
PP Strap Width (mm)	9, 12, 15
Tension Adjustment (kg)	Max. 90
Power Consumption (kw)	1.225
System Dimension (mm)	1653(L)x1440(W)x 1715(H)



ITW Signode
Packaging Solutions
Equipment • Consumables • Services

ITW India Limited
Industrial Packaging Systems Group
401 & 402 New Udyog Mandir
Moghul Lane, Mahim
Mumbai-400 016, India
Tel: 91-22-2444 9022/9052, 5551 1235
Fax: 91-22-2444 9021
Email: info@itwindia.com

The company has policy of continuous product development and reserves a right to alter specifications at any time without prior notice.

Branches: Bangalore: 22240490 / 22242304, Baroda: 2322495/6/7, Bhilai: 2392592/2392172, Coimbatore: 2212045, Chennai: 24723863 / 24725313, Jamshedpur: 2700399, Kolkata: 24618014/8020 Mumbai: 24449022/9502, Navi Mumbai: 27725740/6524, New Delhi: 26424984/26428646, Pune: 39505952, Rourkela: 2470757.