

TECHNICAL DATA SHEET

Trikol- Porous primer

Description:

Primer for use with TRIKOL PS 65G- Gun Grade ,TRIKOL PS 65P- Pour Grade ,Trikol 1kPU ,Trikol PU-pour and Trikol 2150

- 1) Concrete Surfaces
- 2) Natural Stone
- 3) Bricks & Stained Timber Frame
- 4) Glazed Tile (Unglazed edges).

Application:

By Brush or Spray, Take required quantity from original container to small bowl for use. The container must be closed as soon as possible.

This product is hygroscopic in nature.

Packing:

1 X 250 ml Aluminium bottle.

Storage and Shelf life

Store under cover, out of direct sunlight and protect from extremes of temperature. In tropical climates the product must be stored in an air-conditioned environment.

Shelf life is 12 months when stored as above

Technical Information – Typical Data

Appearance	: Clear liquid
Colour	: Straw
Odour	: Solvent
Density	: 0.95 @ 25DegC

Health and Safety

Ensure that protective gloves, overalls and protective footwear are worn at all times when handling the material. Avoid skin contact. Should the material come in contact with the skin it may be removed with soap and warm water. If discomfort continues, seek medical advice. If product comes in to contact with eyes, rinse with plenty of fresh water and seek medical advice.

Technical Support

Tri Polarcon provides technical advisory service supported by terms of specialist in the field

Disclaimer

The Company's Products are sold subject to the Company's Standard Terms and Conditions of Sale. Products are warranted against defective materials and workmanship. The Company makes every effort to ensure that all the information, recommendations or the specifications provided by it are accurate and true. However as the Company has no control over the conditions of use, it cannot accept any liability, either directly or indirectly regarding the usage of its products. Product specifications are subject to change without prior intimation to users as the products are being continuously upgraded.

Mfg.by-

TRI POLARCON PVT. LTD.

Mfg of Epoxy floor coatings, Sealants, Waterproofing chemicals & Construction Chemicals.

Survey No. 38/1, Rajlaxmi Industrial Estate, Narhe, Pune-411041.

Contact No.9970633366/9822167282/9049800090.

www.tripolarcon.com/Email:tripolarcon@gmail.com