



Safety Shoe

MODEL TANGO HR 300 AK



COMPONENT	FEATURE	BENEFIT
UPPER	Genuine grain leather. Thickness : 1.8 - 2.00 mm.	Breathable , highly flexible, extra strong for comfort and long time usage.
DESIGN :	Jodhpuri	For extra protection and comfort of the ankle
LINING :	Padded Synthetic	Aesthetic appearance, good comfort, breathable for perspiration control.
SOCKS :	Fabric laminated EVA.	Breathable and extra cushion for comfort.
INSOLE :	Non-woven (pocket type)	Extra thick insole for safety & flexibility.
SOLE :	Vulcanised Nitrile rubber sole.	Vulcanised Nitrile rubber can withstand temperature of 300° C for 1 minute. Highly flexible and low abrasion.
TOE CAP :	Wide Alloy Steel toe	Light weight / Rust free with an ability to withstand an impact of 200 J as per IS - 15298.
COUNTER /STIFFENER :	Non-woven	Soft and Tough to give cushion as well as shape and strength at the heel part of the shoes.
THREADS :	3 Ply / 6 Ply nylon.	To make the uppers strong at all the joints and inturn enhances the looks and life.
EYELETS :	D-ring type	Coated to make them more appealing as well as 100 % rust free.
LACES:	Nylon	Double color rowel laces for easy grip and aesthetics.
MARKING	近 IS:15298 PART 2 CM/L3069354	

Udyogi Plastics Pvt. Ltd.

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 Tel. : +91 33 2225 1470/71/72 > Fax : +91 33 2225 1486 E-mail : corp@udyogi.net > Website : www.udyogisafety.com

- mumbai@udyogi.net delhi@udyogi.net
- chennai@udyogi.net > orissa@udyogi.net
- abd@udyogi.net

- noida@udyogi.net