

Datasheet

Safety Shoe

MODEL TANGO HR 300 EX



COMPONENT	FEATURE	BENEFIT
UPPER	Genuine grain leather. Thickness: 1.8 - 2.00 mm.	Breathable , highly flexible, extra strong for comfort and long time usage.
DESIGN:	Derby	Low cut design for executive look and superb fit.
LINING:	Padded Synthetic	Aesthetic appearance, good comfort, breathable for perspiration control.
SOCKS:	Fabric laminated EVA.	Breathable and extra cushion for comfort.
INSOLE:	Non-woven (pocket type)	Extra thick insole for safety & flexibility.
SOLE:	Vulcanised Nitrile rubber sole.	Vulcanised Nitrile rubber can withstand temperature of 300° C for 1 minute. Highly flexible and low abrasion.
TOE CAP:	Wide Alloy Steel toe	Light weight / Rust free with an ability to withstand an impact of 200 J as per IS - 15298.
COUNTER/STIFFENER:	Non-woven	Soft and Tough to give cushion as well as shape and strength at the heel part of the shoes.
THREADS:	3 Ply / 6 Ply nylon.	To make the uppers strong at all the joints and inturn enhances the looks and life.
EYELETS:	Brass	Coated to make them more appealing as well as 100 % rust free.
LACES:	Nylon	Single color rowel laces for easy grip and aesthetics.
MARKING IS:15298 PART 2 CM/L3069354		

Udyogi Plastics Pvt. Ltd.

294, B. B. Ganguly Street, 2nd Floor, Kolkata - 700 012 Tel.: +91 33 2225 1470/71/72 > Fax: +91 33 2225 1486 E-mail: corp@udyogi.net > Website: www.udyogisafety.com

▶ mumbai@udyogi.net → delhi@udyogi.net

▶ chennai@udyogi.net → orissa@udyogi.net

▶ abd@udyogi.net

noida@udyogi.net