



Switches


Description	Ref Code for WH	MRP WH	Ref Code for CG	MRP CG	Std. Packing
6A 1-Way	X1001WH	69	AAKY1001	78	10
6A 1-Way W / Indicator Lamp	X1081WH	97	AAKY1081	111	10
6A 2-Way	X1002WH	83	AAKY1002	95	10
16A 1-Way	X1101WH	95	AAKY1101	119	10
16A 1-Way W / Indicator Lamp	X1181WH	130	AAKY1181	149	10
16A 2-Way	X1102WH	123	AAKY1102	142	10
6A 1-Way Switch, 2 Module	X1021WH	100	AAKY1021	112	10
16A 1-Way Switch, 2 Module	X1121WH	124	AAKY1121	138	10
6A 1-Way Switch, 2 Module with Indicator	X1028WH	130	AAKY1028	145	10
16A 1-Way Switch, 2 Module with Indicator	X1128WH	149	AAKY1128	162	10
20A DP W / Indicator Lamp	X1286WH	195	AAKY1286	214	10
32A DP Switch	AAKX1232	319	—	—	10



X1001WH, X1002WH
X1101WH, X1102WH




X1021WH
X1121WH




X1081WH
X1181WH




X1286WH
X1028WH
X1128WH



X1005WH



X1025WH



X1085WH

Bell Push

Description	Ref Code for WH	MRP WH	Ref Code for CG	MRP CG	Std. Packing
6A Bell Push	X1005WH	95	AAKY1005	108	10
6A Bell Push (2 M Size)	X1025WH	120	AAKY1025	138	10
6A Bell Push W / Indicator	X1085WH	107	AAKY1085	123	10
6A Bell Push W / Indicator (2 M Size)	X1086WH	132	AAKY1086	148	10

Socket

Description	Ref Code for WH	MRP WH	Ref Code for CG	MRP CG	Std. Packing
6A 2-Pin / 3-Pin (Shuttered)	X2005WH	103	AAKY2005	120	10
6A 'Uni Socket' (Shuttered)	X2007WH	118	AAKY2007	140	10
16A 3-Pin (Shuttered)	X2103WH	164	AAKY2103	188	10
6A / 16A 3-Pin (Shuttered)	X2106WH	148	AAKY2106	170	10
13A BS Flat-Pin (Shuttered)	X2403WH	193	AAKY2403	223	10
20A 3-Pin Socket Outlet with Shutter	X2206WH	180	AAKY2206	217	10
25A 3-Pin Socket Outlet with Shutter	X2207WH	196	AAKY2207	226	10
13A Multi-Pin Socket Outlet with Shutter	X2010WH	170	AAKY2010	195	10




X2005WH



X2007WH



X2010WH



X2103WH



X2106WH



X2403WH

Range Features

- Hybrid switch uses combination of ABS and PC as raw material for excellent finish and thermal insulation.
- Switch conforms to the IS 3864:1997.
- Socket conforms to IS 1293:1987.
- RJ-45 socket-contacts are gold plated.
- Ceiling Fan Regulator provides five distinctive speed, totally hum free.
- Satin finish; easy to clean.
- Child proof sockets.
- Captive screws for faster installation.
- Shrouded terminals for complete safety.
- In-line centre terminal reduces the installation time.
- Snap-in and snap-out type of fixing for ease of installation. No screw required for fixing.
- Fixing of insert from the front.