



ENGAGE INDUSTRIES PRIVATE LIMITED

Established in 2021, 'Engage Sprays' is set to be one of the segment leaders. We have launched wide range of spray cans of Quick Drying Paints & Corrosion Resistant Products required in various industries. We Provide innovative solutions for the most demanding industrial and MRO applications. Our products are designed to meet the needs of today's industrial maintenance professional. We have skills and harmonious blending methods used to blend the mixture for best quality and long-lasting products.

Our focus on continuous improvement has been the driver in developing products which will help our customers

- Preserve & protect their valuable equipment.
- Become more efficient/ more productive/ more profitable.



Our Product range consists of Quick drying paint Sprays, Corrosion Resistance Sprays, DPT testing Sprays, Electric Maintenance Sprays, Industrial Lubricant and Cleaner Sprays, etc.

Advantages for using Engage Products : Quick drying, High gloss, High corrosion resistance, Ideal for use in interior and exterior environment.

Corrosion Resistant Aerosols

	Properties	Applications	Size
Air Drying Spray Paint	Dry time 2-3 Mins, Withstand up to 115° C, 475 hrs. salt spray resistant. UV resistant.	Used for touchup for powder coated/ painted surfaces. Available in all RAL & std shades	400ml
Zinc Matt (Galvanizing Spray)	Pure zinc flake coating, Dry time 2-3 Mins, Zinc 99%, 475 hrs. salt spray resistant	Touch up application for galvanized surfaces.	500ml
Zinc Glossy (Galvanizing Spray)	Pure zinc flake coating, Dry time 2-3 Mins, Zinc 99%, 475 hrs. salt spray resistant	Touch up application for galvanized surfaces.	500ml
Zinc Primer	Dry time 2-3 Mins, Withstand up to 115° C, 98 hrs. salt spray resistant.	Used for any surface as primer coat	400ml / 500ml
Zinc Coat	Dry time 15 Mins, Withstand up to 115° C, 475 hrs. salt spray resistant.	Used as cold galvanizing.	1 & 4 Liter pack
Bronze Glaze Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Used for Touchup application for antique finishes	400ml
Copper Glaze Spray	Dry time 2-3 Mins, Withstand up to 180° C, 155 hrs. salt spray resistant.	Touch up application for brazed surfaces. Antique finishes	400ml
Silver Glaze Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Touch up application for blue passivated, zinc plate surfaces. Antique finishes	400ml
Gold Glaze Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Touch up application for Antique finishes	400ml
Stainless Steel Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Touch up application for Stainless Steel surfaces.	500ml
Chrome Glaze Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Touch up application for Stainless Steel & Mild Steel surfaces.	400ml
Clear Lacquer Spray	Dry time 2-3 Mins, Withstand up to 115° C, 155 hrs. salt spray resistant.	Used for bare surface or painted surfaces without changing its look	400ml
HT Paint Spray	Dry time 5-6 Mins, Withstand up to 600° C, 155 hrs. salt spray resistant.	Used for automotive silencers, Industrial chimneys. Available in black and Aluminum shades	400ml



Aerosols for dye penetrant test

	Properties	Applications	Size
DPT Cleaner	Quick oil and dirt cleaning	1 st step of DPT : Cleaning Surface	500ml
DPT Penetrant	Good Penetrating, Easily gets inside small cracks, Red appearance.	2 nd step of DPT: Spray on surface to be tested.	500ml
DPT Developer	Easily detects cracks, White appearance.	3 rd step of DPT: Spray with Developer to easily see minute cracks and blow holes	500ml

Lubricating Aerosols

	Properties	Applications	Size
HT Lubricating Spray	Ensures good lubrication at high temperature up to 300°C. High resistance to dust absorption and water wash off.	Used where lubrication is required at high temperature. Commonly used in chain sprocket lubrication	400ml
Antiseizure Lubricant Spray	Rust dissolving, Multipurpose, Water displacement lubricant	Used on rusted or seized parts to dissolve rust, also used to prevent rusting	400ml
Anti-Spatter Spray	Chemically inert lubricant, High temperature resistant.	Sprayed on component before welding to avoid spatters of welding to be formed on welded components and welding nozzles.	400ml

Electric Maintenance Sprays

	Properties	Applications	Size
Eleclean 88	Electrical contact cleaner. Ideal for removing grease, oil, dirt. Prevents corrosion, Plastic, rubber, paint safe.	Used to clean delicate electric contacts, Switchgears etc.	400ml
PCB Cleaner	Removes grease, tarnish, oxidation. Helps prevent corrosion, fast drying. Rubber, Plastic, paint safe, Moisture removing property.	Used to clean delicate electronic components, PCBs etc.	400ml
Insulating Warnish Spray	Provides good resistance to transformer oil & moisture, Quick drying, Provides tough insulating seal.	Used to seal electric leakage path for electric motor, battery terminals.	400ml



Manufactured in India



**ENGAGE INDUSTRIES
PVT LTD.**

Contact Us:

Email : info@engagesprays.com
 Webdite : www.engagesprays.com
 Customer Care : +91 87937 34533