



DEFOAMER

Grade Ref: Foamtrap 2722

Foamtrap 2722 contains silicone and silica particles allow rapid de-foaming effect in resins like Epoxy, PU and Acrylics. It produces instant de-aeration and defoaming properties at much lower dosage. Foamtrap 2722 also acts as a leveling agent giving a smooth surface to the coating.

Typical Properties

Form.White viscous liquid
Active content.....100%
Chemistry.....Silicone emulsion
Specific Gravity g/cc.....1.06

Addition & Usage

0.5% - 1% on total formulation.

Under normal conditions, the dosage is max of 1.0% for solvent-free system and 0.3% for solvent-based system, based on total formulation.

End use applications

- Water borne coatings & Inks
- Solvent borne coatings & inks
- Floor polishes
- Adhesive & Sealants
- De-greasers & Cleaners

Packaging

25 kg Pail

1000 Kg IBC Tote

Shelf life

1 year



A-312 Pratik Industrial Estate.
Mulund Goregaon Link road
Bhandup West, Mumbai 400078
India

T- 022 4122 5480
E-mail: info@geoconproducts.com
www.geoconproducts.com
www.geoconproducts.co.in

NOTE: Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product is appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, and whether such use will infringe the intellectual property rights of third parties.