

Technical Data Sheet



DEFOAMER

Grade Ref: FS 155
Based on Fluorosilicone

Foamtrap FS 155 series is high-performance defoamer cum wetting agent is based on Fluorocarbon and Silicone combinations. It provide outstanding ability to reduce surface tension of fresh and brine water with elevated high temperature. FS 155 not only control foam but increase the productivity.

Typical Properties

| Appearance | .Translucent |
|----------------------|----------------|
| Ionic nature | .Non ionic |
| Composition | Fluorosilicone |
| Active content | .5% |
| Solvent | .Ethers/MPA |
| Density @20°C, kg/m3 | .1.10-1.12 |
| pH value (5%, 25°C) | 5-7 |

Key advantages & application

- Effective in low concentration
- Resistance to chemicals and oxidation
- Very low surface tension reduction capacity
- Compatible with freshwater & brackish water
- Easy to mix
- · Act as wetting agent also
- · Works quickly and efficiently

^{*} The typical values presented here are believed to be accurate; they should not, however, be considered to constitute a specification.



Available packaging

25 kg. Pail 275 gallon IBC tote

Limitations

Not effective in muds with excessive gel strengths

Toxicity and Handling

Information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

Shelf life

2 years



A-312 Pratik Industrial Estate. Mulund Goregaon Link road Bhandup West, Mumbai 400078 India T- 022 4122 5480 E-mail: info@geoconproducts.com www.geoconproducts.com www.geoconproducts.co.in

NOTE: Although the data supplied above is believed to be accurate, each user is advised to make an independent determination as to whether the described product is appropriate for a particular use or application, whether such use will comply with all applicable laws or regulations, and whether such use will infringe the intellectual property rights of third parties.