



J. M. Engineering Co.

A Complete Process Control automation

Single Wall Heat Shrink Tubing

Heat Shrink Sleeve



150? Flame retardant heat shrink tubing RSFR-HT(2X)



Features

1. Flame-retardant
2. Good resistance to common fluids and solvents;
3. UL approved
4. Operating temperature:-55?~+150?
5. RoHS compliant

Dimensions

Size		As supplied	After Recovery(mm)		Standard Package
Inch	mm	Internal diameter(mm)	Internal diameter(mm)	Wall thickness(mm)	Spool Length m/spool
3/64	1.2	1.2	0.6	0.33	200
1/16	1.6	1.6	0.8	0.33	200
3/32	2.4	2.4	1.2	0.44	200
3/4	18.0	18.0	6.0	0.85	50
1	24.0	24.0	8.0	1.00	25
1-1/4	30.0	30.0	10.0	1.15	1.22
1-1/2	39.0	39.0	13.0	1.50	1.22
2	50	50	16	2.50	1
	60	60	20	2.60	1
	70	70	23	2.60	1
3	80	80	26	2.60	1
	90	90	30	2.60	1
4	100	100	33	2.60	1

J. M. Engineering Co.

2

Technical Data – Physical

Property	Test Method	Typical Performance
Tensile Strength	ASTM D2671	10.4MPa
Elongation(%)	ASTM D2671	200%

Technical Data – Electrical

Property	Test Method	Typical Performance
Dielectric Strength	IEC 243	=15kv/mm
Volume Resistivity	IEC 93	=1×10 ¹⁴ Ω·?

J. M. Engineering Co.

3